

# KARE KANAL MAKİNESİ TEK GİRİŞLİ

## AUTO DUCT FORMER (1 FEEDER)

**DFC** MAKİNE  
MÜHENDİSLİK



TR

Tasarlamış olduğumuz kare kanal makinesi çift iz, çift sürücü ve düzleştirici özelliği bulunmaktadır.

Kare kanal makinesi PLC sistem sayesinde sac ölçülerinde hata yapmaz.

Hidrolik sistem sayesinde daha güçlü ve performansı yüksek çalışır. Makine kompresör ve hava bağlantısı gerektirmez.

Etiket çıkartma özelliğiyle çıkan ürünleri markalama yaparak sevk edilme esnasında kolaylık sağlar. Böylece makine yüksek performansta kaliteli çalışır.

- Tam otomatik olarak çalışma (PLC Kontrol)
- 2 Adet rulo açıcı
- 2 Adet saca desen verme ünitesi
- 1 Adet sac düzleştirici
- PLC sistem
- Hidrolik sistem
- Etiket çıkartma özelliği(Opsiyonel)
- Üretim hafıza kayıt sistemi

EN

The square duct machine we have designed features double trace, double driver, and a straightener system.

The square duct machine does not make errors in sheet dimensions thanks to the PLC system.

Given the hydraulic system it functions faster and in high performance. The machine does not require a compressor nor an air channel. With the etiquette printing feature and branding the final products it eases throughout the transportation. Thus the machine functions within high quality performance.

- Full Automatic PLC Control
- 2 Pcs of Roll Carrier
- 2 Pcs of Trace Printing Unit Sheet Metal
- 1 Pc of Sheet Metal Straightener
- PLC System
- Hydraulic system
- Etiquette Printing Unit (Optional)
- Production checking memory system

### TEKNİK ÖZELLİKLER

#### TECHNICAL SPECIFICATIONS

GÜÇ / POWER	6Kw
GERİLİM - FREKANS / FREQUENCY	380/400 VAC 50 - 60 hz 3 ph+PE
YAĞLAMA / LUBRICATION	Yarı Otomatik / Semi - Automatic
BÜKÜLEBİLEN KANAL BOYU / BENDABLE DUCT LENGTH	Min 100mmx100mm
ÇALIŞMA HIZI / WORKING SPEED	200x200mm Kanal İmalat Hız 1 dk/adet 200x200mm Production Speed 1 min/piece
MAKSİMUM ÜRETİM KAPASİTESİ / MAX. PRODUCTION SPEED	120 m <sup>2</sup> /saat - 120 m <sup>2</sup> /hour
BÜKÜLEBİLEN KANAL TİPİ / BENDABLE DUCT TYPE	Düz sac, L tipi kanal, Kare kanal, S tipi kanal Flat sheet metal, L type duct, U type duct, Square duct, S type duct
KENET TİPLERİ / CLAMP TYPES	Pittsburg, Snaplock, Nulcok
RULO AÇICI ÜNİTE KAPASİTESİ / UNCOILER UNIT CAPACITY	İç Çap: Q 500mm max, Sac Eni: 1500mm, Rulo Ağırlığı: 5 Ton Inner Diameter:Q 500mm Sheet Width:1500mm Roll Carrier Weight:5 Tons
SAC KALINLIKLARI / SHEET THICKNESS	0.50 - 1,2mm Galvaniz / 0.5 - 1mm Paslanmaz From 0.50mm to 1,2mm / Galvanised From 0,5mm to 1mm Stainless Steel
DESEN MODELLERİ / TRACE TYPES	Trapez Desen - Z Desen / Trapeze Pattern - Z Pattern
HİDROLİK YAĞ MİKTARI / HYDRAULIC OIL LEVEL	90L

**STOK ADI**  
STOCK NAME

KARE KANAL MAKİNESİ (1 GİRİŞLİ 1250'LİK 2x5 TON RULO TAŞIYICILI)  
AUTO DUCT FORMER MACHINE ( ONE ENTRANCE-1250 WITH 2X5 TON ROLL CARRIER)

**STOK KODU**  
STOCK CODE

DFC KKM 0003