



OVAL ÖLÇÜ SIZE	ÇAP DIAMETER	M ²	OVAL ÖLÇÜ SIZE	ÇAP DIAMETER	M ²	TEKNİK ÖZELLİKLER TECHNICAL SPECIFICATIONS	
150x400	355	1,11	300x465	400	1,26	GÜÇ POWER	22Kw-380V
150x555	400	1,26	300x545	450	1,41	SAC KALINLIĞI METAL SHEET THICKNESS	0,5-1,2mm
150x630	450	1,41	300x625	500	1,57	ÇALIŞMA ARALIĞI OPERATING RANGE	0-3000mm
150x710	500	1,57	300x720	560	1,76	ÜRETİM HIZI PRODUCTION SPEED	10m/dak
150x805	560	1,76	300x830	630	1,98	HİDROLİK YAĞ MİKTARI HYDRAULIC OIL LEVEL	200L
150x915	630	1,98	300x960	710	2,23	HİDROLİK GÜÇ HYDRAULIC POWER	300 Ton/Tons
150x1045	710	2,23	300x1100	800	2,51		
150x1185	800	2,51	300x1260	900	2,83		
150x1345	900	2,83	300x1415	1000	3,14		
150x1500	1000	3,14	300x1605	1120	3,52		
150x1690	1120	3,52	300x1815	1250	3,93		
150x1900	1250	3,93	350x520	450	1,41		
200x455	355	1,11	350x595	500	1,57		
200x525	400	1,26	350x690	560	1,76		
200x605	450	1,41	350x805	630	1,98		
200x685	500	1,57	350x930	710	2,23		
200x780	560	1,76	350x1070	800	2,51		
200x890	630	1,98	350x1225	900	2,83		
200x1015	710	2,23	350x1570	1120	3,52		
200x1160	800	2,51	350x1775	1250	3,93		
200x1315	900	2,83	400x570	500	1,57		
200x1475	1000	3,14	400x665	560	1,76		
200x1665	1120	3,52	400x775	630	1,98		
200x1870	1250	3,93	400x900	710	2,23		
250x495	400	1,26	400x1045	800	2,51		
250x575	450	1,41	400x1200	900	2,83		
250x655	500	1,57	400x1545	1120	3,52		
250x750	560	1,76	400x1750	1250	3,93		
250x860	630	1,98	450x635	560	1,76		
250x985	710	2,23	450x745	630	1,98		
250x1130	800	2,51	450x870	710	2,23		
250x1290	900	2,83	450x1015	800	2,51		
250x1445	1000	3,14	450x1170	900	2,83		
250x1635	1120	3,52	450x1515	1120	3,52		
250x1840	1250	3,93	450x1720	1250	3,93		

TR

Tam otomatik oval kanal makinesi, hızlı bir şekilde yuvarlak kanalları oval kanallara dönüştürür. 0,5 mm'den 1,2 mm'e kadar büküm kapasitesine sahiptir. 150 mm'den 450 mm çapa kadar olan standart bütün oval kanalların üretimi için gerekli kalıplara sahiptir. Makine kontrolü PLC tarafından yapılır ve Ovalizör gerekli gücü sağlamak için üstün hidrolik ünite ile donatılmıştır.

EN

Oval duct forming. It transforms the round spiral ducts fastly. It has a bending capacity of up to 0.5 mm - 1.2 mm. It has all required oval ducts production standarts mold ranging from 150 mm - 450 mm. The machine control is done by PLC and in order for the oval machine to supply the necessary power it encompasses an advanced hydraulic unit.

STOK ADI
STOCK NAMESTOK KODU
STOCK CODEOVAL KANAL MAKİNESİ
OVAL DUCT FORMING
MACHINE

DFC OKM 0001

